

NEW HOLLAND TRACTORS – 25 HP to 670 HP



COMPACT & SMALL UTILITY TRACTORS UP TO 100HP



Boomer | 25-50hp

3pl: 1250kg | PTO: 540 | HYD: 1
Synchro or Hydro | 25km/hr
FEL: 1.8m, 440kg | CAB/ROPS



Workmaster | 38hp

Backhoe Option | PTO: 540 | HYD: 1
Hydro 3 speed | 24km/hr
FEL: 2.4m, 740kg | ROPS



TT4 | 55-90hp

3pl: 2500kg | PTO: 540/540E | HYD:3
Synchro 12x12 | 34km/hr
FEL = 3.3m, 2040kg | ROPS



T4S | 55-75hp

3pl: 2700kg | PTO: 540/540E | HYD:3
Synchro 40km 12x12 | 36km/hr
FEL: 3.1m, 1584kg | CAB



TD5 | 75-110hp

3pl: 3565kg | PTO: 540/540E | HYD:3
Shuttle 12x12 | 38km/hr
FEL: 3.6m, 2630kg | CAB/ROPS



T5 Dual Command | 85-115hp

3pl: 4364kg | PTO: 3 speed | HYD: 3
Dual Command 24x24 | 29km/hr
FEL: 3.6m, 2630kg | CAB/ROPS

SPECIALITY VINEYARD & VITICULTURE TRACTORS UP TO 150HP



T3F | 50-72hp

3pl: 2277kg | PTO: 540/540E | HYD:3
Synchro 37km 20x20 | 37 km/hr
Min Width: 1440mm | ROPS



TK4.100 | 99hp

3pl: 3620kg | PTO: 540/1000 | HYD:4
Mech 8x8 Trans | 12km/hr
450mm SmartTrax | CAB / ROPS



TDD High Clearance | 98hp

3pl: 3565kg | PTO: 3 speed | HYD: 3
Synchro 20x12 Creeper | 29km/hr
Ground Clearance = 610mm | CAB



TS6 High Clearance | 118hp

3pl: 3640kg | PTO: 540/1000 | HYD: 4
Creeper 24x12 Trans | 30km/hr
637mm Ground Clearance | CAB/ROPS



T4F, T4N & T4V | 75-105hp

3pl: 2600kg | PTO: 540/540E/1000 | Synchro or Dual Command Trans 38km/hr
Min Width: T4F = 1,556mm | T4N = 1,229mm | T4V = 1,061mm
Min Height: T4F = 2,173mm | T4N = 2,173mm | T4V = 2,148mm



LEGEND:

HYD = Hydraulic remotes (listing maximum remote option)

FEL = Front End Loader (listing maximum lift height and weight at loader pivot pins)

MEDIUM UTILITY TRACTORS UP TO 150HP



T5 Electro Command | 95-115hp
 3pl: 5424kg | PTO: 3 speed | HYD: 3
 Electro Command 16x16 | 42km/hr
 FEL: 3.6m | 2630kg | CAB



T6 | 110-131hp | (143-163hp)
 3pl: 5284kg | PTO: 3 speed | HYD: 4
 Auto Command (CVT) | 50km/hr
 Sidewinder + Intelliview III Display
 FEL: 4.2m, 3171kg



T6000 | 112-141hp (142-178hp)
 3pl: 7864kg | PTO: 3 speed | HYD: 4
 Electro Command 16x16 | 38km/hr
 SPEC: LS / PLUS / ELITE
 FEL: 4.2m, 3171kg

HEAVY UTILITY TRACTORS UP TO 240HP



T6080 | 155hp (193hp)
 3pl: 6668kg | PTO: 3 speed | HYD: 4
 Range Command 19x6 | 50km/hr
 FEL: 4.2m, 3171kg
 Standard / Super Steer / Terraglide



T7SWB | 140-180hp (175-225hp)
 3pl: 7855kg | PTO: 3 speed | HYD: 6
 Power or Auto Command | 50km/hr
 Classic or Sidewinder Console
 FEL: 4.5m, 3378kg



T7LWB | 180-240hp (225-270hp)
 3pl: 7138kg | PTO: 4 speed | HYD: 6
 Power or Auto Command | 50km/hr
 Classic or Sidewinder Console
 FEL: 4.5m, 3378kg

HIGH HORSEPOWER TRACTORS ABOVE 240HP



T7 HD | 270-300hp (288-313HP)
 3pl: 10140kg | PTO: 4 speed | HYD: 6
 Auto Command | 50km/hr
 Sidewinder + Intelliview IV Display



T8 | 250-380hp (320-435hp)
 3pl: 9026kg | PTO: 540/1000 | HYD: 6
 Auto / Ultra Command | 50km/hr
 Sidewinder + Intelliview IV Display



T8 | 340-379hp (409-435hp)
 Track Spacing: 1.9m - 3.9m
 Auto / Ultra Command | 30km/hr
 SmartTrax: 18" or 24"



T9 | 405-600hp (446-670hp)
 3pl: 9071 opt | PTO: 1000 opt
 Auto / Ultra Command | 40km/hr
 HYD: 8 @ 212Lpm (427Lpm opt)



T9 | 542-600hp (613-670hp)
 Intellishift | 13km/hr
 HYD: 8 @ 212Lpm (427Lpm opt)
 SmartTrax: 36"



LM7.42 ELITE | 7m | 4.2t
 140HP | Hydro PowerShift | 38km/hr
 HYD: 140Lpm | Joystick = all controls
 Manitou / JCB Hitch opt

LEGEND:

HYD = Hydraulic remotes (listing maximum remote option) | HP = Rated & (Engine Power Management Boost)
 FEL = Front End Loader (listing maximum lift height and weight at loader pivot pins)

HARVEST



CR | 410-620hp (450-680hp)
 22" Twin pitch rotors | 14,500L Tank
 Auger: 12m CTF | Adjust Rotor Vanes
 IntelliSense – LIVE Auto Settings

VARIFEED | 30', 35' & 40'
 Telescopic floor: 575mm | Single reel
 Auger: full width retractable fingers
 Cereal | Canola direct head | Pulse

790C15 | 15 foot
 Mechanical floatation | 30cm flex
 2 speed Auger: 160-187rpm
 Pickup & Transfer draper belt

HAY EQUIPMENT



210 Discbine | 3.16m (10ft)
 Cutterbar: Modular | HYD tilt
 Conditioning: Rubber / Steel / Flail
 Hitch: Drawbar / 2 point

Discbine | 4-4.95m (13ft – 16ft)
 Cutterbar: Modular | HYD tilt
 Conditioning: Rubber / Steel / Flail
 Hitch: Drawbar / 2 point

Speedrower | 126-226hp
 Hydro Dual range | 26km/hr
 IntelliView IV | Cab Suspension
 Headers: Sickle / Draper / Disc



BC 5060/5070 | (18in x 14in)
 BC5060 = 61hp | BC5070 = 76hp
 2m pickup | Knotter lube kit
 HYD drawbar swing | Bale extension

RB 150/180 | 5ft – 6ft
 SuperFeed / CropCutter | Auto Lube
 Drop Floor | IntelliBale | 1.3m Twine
 Hay / Straw / Silage | Moisture Sensor

BB1290 Plus | 3' x 4'
 Packer / CropCutter | 130-160hp Plus
 ActiveWeigh Scales | Moisture Sensors
 IntelliView IV | Auto Lube

PRECISION LAND MANAGEMENT (PLM) EQUIPMENT



IntelliView III Display



IntelliView IV Display




EZ-Guide® 250 Display



FM-750 Display



On The Go ActiveWeigh™ System




Combine Yield Mapping



Real Time Combine Moisture Sensing



FM-1000 Display



XCN-2050™ Display



NH 372 Receiver



PLM Displays

XCN-2050: Full capability
 XCN-1000: Auto Guidance tablet
 FM750: Auto Guidance basic
 FM250: Visual Light bar only
 IntelliView III: OEM control
 IntelliView IV: OEM Guidance

Guidance & Steering

IntelliSteer: Through OEM system
 EZ-Pilot: Electric Steering wheel
 EZ-Steer: Side mount motor
 Autopilot: High spec Electric wheel
 NH 372 Receiver: OEM Receiver
 RTK Base Station: RTK Correction

Harvest Solutions

Combine yield mapping
 Combine moisture, protein, oil
 Baler moisture sensing
 Baler ActiveWeigh Scales
 IntelliSense Auto header settings

